

FORMULA X ULTRA HIGH PERFORMANCE STRIPPER

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Formula X UHP (Ultra High Performance) Stripper Product Number: 503
 Product Type: Non-ammoniated, ultra high performance stripper

Manufacturer Address:

Amano Pioneer Eclipse Corporation
 P.O. Box 909
 1 Eclipse Road
 Sparta, NC 28675

Contact Information:

Telephone: 1-336-372-8080
 Email: msds@pioneer-eclipse.com
 Internet: www.pioneer-eclipse.com

FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure or Accident. Call CHEMTREC Day or Night.
 Within USA and Canada 1-800-424-9300. Outside USA and Canada 1-703-527-3887 (collect calls accepted)

2: HAZARDS IDENTIFICATION

OSHA status: Hazardous- Corrosive

Precautions: Danger. Combustible. Corrosive to skin and eyes. Keep container closed when not in use. Keep out of reach of children.

Potential Health Effects:

Eye Contact: Causes eye burns. May cause permanent damage.

Skin Contact: Causes skin burns. May cause permanent damage.

Inhalation: May be harmful if inhaled. May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion: Harmful if swallowed. May cause burns to mouth, throat and stomach.

Health:	3
Flammability:	2
Reactivity:	0

3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS Number	Weight %
ethylene glycol monobutyl ether	111-76-2	10 - 30
monoethanolamine	141-43-5	5 - 10
propylene glycol monobutyl ether	5131-66-8	5 - 10

4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eye with plenty of water for at least 15 minutes. (If easy to do, remove contact lenses, if worn). Get medical attention immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes awhile removing contaminated clothing and shoes. Get medical attention immediately.

Inhalation: If breathing is difficult. Remove subject to fresh air. Seek medical attention immediately.

Ingestion: Call a physician or poison control center immediately. Do not induce vomiting. Seek medical advice immediately.

5: FIRE FIGHTING MEASURES

Extinguishing Media: Water spray, CO₂, dry chemical, alcohol-type or universal type foams

Special Fire Fighting Procedures: Corrosive liquid. (See Sections 8 and 10.) Do not spray a solid stream of water or foam directly in hot liquid. This may cause frothing. Fire fighters should wear NIOSH approved breathing apparatus.

Hazardous Combustible Products: None known

Unusual Fire and Explosion Hazards: Materials can splatter above 100° C / 212° F

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Put on appropriate personal protective equipment (see Section 8). Keep spectators away. Floors may be slippery; use care to avoid falling.

Environmental Precautions: Keep spills and cleaning run-off out of sewers and open bodies of water.

Containment and Clean-Up

Small Spills: Absorb spill with inert material (e.g. sand, earth) and dispose of as waste material in accordance with local, state and federal regulations.

FORMULA X ULTRA HIGH PERFORMANCE STRIPPER

Large Spills: Neutralize spill area. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal.

Waste Disposal: Landfill or incinerate the contaminated solids and diking material in accordance with local state and federal regulations concerning disposal of hazardous materials. Non-salvageable liquid should be drummed and turned over to a licensed hazardous waste disposal facility.

7: HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only in well-ventilated areas. Avoid breathing vapors or mists. Remove and wash contaminated clothing and footwear before re-use.

Storage: Storage temperature (Max. 60°C/140°F - Min. 1°C/34°F)

Other information: Keep from freezing, product may coagulate. Keep container sealed when not in use. Keep out of reach of children.

8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limit Values

Ingredient	CAS Number	ACGIH		OSHA	
		TWA	STEL	TWA	STEL
ethylene glycol monobutyl ether	111-76-2	20 ppm (BEI)	N/L	50 ppm (skin)	N/L
monoethanolamine	141-43-5	3 ppm	6 ppm	3 ppm	N/L

Engineering Controls: Ensure adequate general ventilation.

Personal Protective Equipment (PPE)

Eye/Face Protection: Chemical splash goggles (ANSI Z87.1-1989 or approved equivalent)

Skin Protection: Rubber gloves recommended. If major exposure is possible, wear suitable protective clothing such as rubber boots, apron, etc.

Respiratory Protection: None required when permissible airborne concentrations are not exceeded. In an emergency, use approved positive pressure self-contained breathing device.

9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: clear, liquid	Odor: citrus
Odor Threshold: N/E	pH: 12.2 ± 0.5
Freezing Point: 32°F / 0°C	Boiling Point: 212°F / 100°C
Flash Point: 150°F / 66°C (ASTM D56)	Evaporation Rate: less than water
Viscosity: < 10 cps @ 68°F	Upper/Lower Flammability limits: N/A
Vapor Pressure: less than water	Vapor Density: greater than air
Relative Density: 8.3 lb/gal @ 68°F / 1.0 kg/l @ 20°C	Solubility: 100% soluble in water
Partition Coefficient (n-octanol/water): N/E	Auto Ignition temperature: N/E
Decomposition Temperature: N/E	Volatile by Weight: 92 - 95%

10: STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Hazardous reactions: Adding water directly to the product may generate heat and cause product to splash. To avoid adverse reaction, always add product to water, do not add water to product.

Conditions to avoid: Improper order of dilution

Incompatible materials: Strong acids and oxidizing agents

Hazardous decomposition products: carbon monoxide, carbon dioxide and nitrogen oxides

11: TOXICOLOGICAL INFORMATION

Acute Toxicity: Not determined on product.

Ingredient	LD50 Oral-Rat (mg/kg)	LD50 Dermal - Rabbit (mg/kg)	LC ₅₀ Inhalation-Rat (mg/l)	Carcinogenicity	CA - Prop 65
ethylene glycol monobutyl ether	470	220	2.21 (4 hr)	IARC 3	N/L
monoethanolamine	1720	1025	N/A	N/L	N/L
propylene glycol monobutyl ether	560	3100	N/A	N/L	N/L

FORMULA X ULTRA HIGH PERFORMANCE STRIPPER

LOCAL EFFECTS

Skin contact: Corrosive. Can cause skin burns.
Eye contact: Corrosive. Can cause eye burns.
Sensitization: None expected
Chronic effects: None expected

SPECIFIC EFFECTS

Carcinogenicity: None known
Reproductive effects: None known
Teratogenicity: None known
Mutagenicity: None known

12: ECOLOGICAL INFORMATION

Ecological data not available.

13: DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, regional, and national regulations.

14: TRANSPORT INFORMATION

Proper Shipping Name: Corrosive liquid, n.o.s (ethanolamine) **Hazard Class:** 8
UN Number: UN1760 **Packing Group:** III

15: REGULATORY INFORMATION

U.S. Regulations/Reporting:

Ingredient	CAS Number	SARA 302/304	SARA 313	CERCLA
ethylene glycol monobutyl ether	111-76-2	N/L	1.00%	N/L

State Right to Know Status:

Ingredient	CAS Number	MA - RTK	NJ - RTK	PA - RTK	RI - RTK
ethylene glycol monobutyl ether	111-76-2	present	present	present	present
monoethanolamine	141-43-5	present	present	present	present

Canada Regulations/Reporting

WHMIS Hazard Symbol:



WHMIS hazard class: E B3

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations (CPR)* and the MSDS contains all of the information required by the *CPR*.

Ingredients required for disclosure:

Ingredient	CAS Number	Weight %	Classification
ethylene glycol monobutyl ether	111-76-2	> 1%	B3, D1A, D2B
monoethanolamine	141-43-5	> 1%	B3, E
propylene glycol monobutyl ether	5131-66-8	> 1%	B3, D2B

16: OTHER INFORMATION

Abbreviations Used:

N/E - Not Established
 N/L - Not Listed

N/A - Not applicable
 IARC 3- Unclassifiable as to Carcinogenicity in Humans.

Revision History:

04/01/2011- format change to ANSI Z400.1-2004

Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) or the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnish of such information.

This MSDS has been provided to you in accordance with the OSHA Hazard Communication Standard (29CFR1910.1200).

****IMPORTANT SAFETY INFORMATION**DO NOT DISCARD**PLEASE ROUTE TO COMPANY SAFETY OFFICER****